## Jay Industries, Inc. Crane Test

Name:	•		Date:
Metals:	Plastics:	Department:	Shift:
1. T F_ and pulleys.	Reeving is	the configuration of wire ro	be that lifts the hoist, including the drum, blocks,
2. T F_	It is ok to	use a hoist to transport a pers	son long as the operator is properly trained.
	g in the area, is		ossibility of personal injury to the operator and pment and using SAFE OPERATING
4. T F_ maintenance.	Safe opera	ating practices include a prog	ram of periodic inspection and preventative
5. TF_	To operate	e a crane or hoist you must be	e authorized, trained, and over 18 years old.
6. T F_ there is no rep			t or the spring is broken, it should be used only if
7. T F_ materials.	When rep	airing or maintaining a hoist,	use only manufacturer's recommend parts and
8. T F_ grinding, or v		d remove a crane for service	if it is making peculiar sounds, like squealing,
9. T F_	You shou	d avoid swinging the load or	load hook when traveling the hoist.
10. T F_ no one would		d conduct lifting operations	n such a manner so that if there were a failure,
11. T F_	People are	allowed to walk under a loa	d if they are wearing hard hats.
12. T F_ and rig slings		ed and authorized operators	shall be permitted to operate cranes and hoists
13. T F_	You shoul	d never lift or transport a loa	d until all personnel are clear.
14. T F_	If the hois	t fails any part of the inspect	on, tag it defective and notify your supervisor.
15. T F_	It is ok to	use a chain or rope as ground	for welding.
16. T F_	It will not	hurt the crane to start and sto	p it suddenly.
I	cranes and lor the safe use	_certify that Jay Industries p noists. I fully understand t and operation of power drive	rovided me with training in the safe operation of he material provided, and intend to follow the n cranes and hoists at Jay Industries, Inc.